

# **Intercontinental Chemical Corporation**

4660 Spring Grove Avenue, Cincinnati, Ohio 45232 \* 513-541-7100 \* fax 513-541-6880

## SAFETY DATA SHEET

# ICC 942 SPRAY / WIPE™

## **SECTION 1: PRODUCT AND COMPANY IDENTIFICATION**

Product Name: ICC 942 Spray/Wipe™

Manufacturer: INTERCONTINENTAL CHEMICAL CORPORATION

Address: 4660 Spring Grove Avenue, Cincinnati, OH USA 45232-1995 Emergency Phone: 513-541-7100 (business hours 8am-5pm Eastern Time) Chemtrec Phone: 800-424-9300 (after business hours) Ref. CCN 11409

Fax Phone: 513-541-6880 Chemical Family: Solvent cleaner

Product Use Cleans ink from screen printing mesh

## **SECTION 2: HAZARDS IDENTIFICATION**

DANGER Hazard Category Hazard Classification

1 Aspiration Hazard

2 Skin Corrosion / Irritation

2A Eye Damage / Irritation 3 Flammable Liquids

## PICTOGRAM AND HAZARD STATEMENTS







Causes serious eye irritation. Causes skin irritation. Flammable liquid and vapor. May be fatal if swallowed and enters airways

## **PREVENTION**

Keep away from heat, sparks, open flames and hot surfaces. No smoking.

Keep container tightly closed.

Ground/bond container and receiving equipment.

Use explosion-proof electrical, ventilating, lighting, equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Wash thoroughly after handling.

Wear protective gloves, protective clothing and eye protection or face protection.

## RESPONSE

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

If eye irritation persists or If skin irritation occurs: Get medical advice or medical attention.

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with plenty of water or shower.

IF SWALLOWED: Immediately call a POISON CENTER or doctor; Do NOT induce vomiting.

Take off contaminated clothing and wash clothing before reuse.

In case of fire: Use dry chemical, CO2, water spray or regular foam to extinguish.

### STORAGE

Store in well-ventilated place. Keep cool. Store locked up.

### DISPOSAL

Dispose of contents and container in accordance with local, state and federal regulations.

## **SECTION 3: COMPOSITION / INFORMATION ON INGREDIENTS**

ICC 942 Spray/Wipe is a proprietary product; the specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.

Ingredient: Petroleum distillates Glycol Ethers & Additives

CAS# Proprietary Properitary Wt % <45 >55

Page 1 of 4 Revised July 2018: Effective 7/02/2018

Continued

#### **SECTION 4: FIRST AID MEASURES**

If swallowed: Rinse mouth. Do NOT induce vomiting.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

If on skin or hair: Immediately take off all contaminated clothing. Rinse skin with water or shower.

If inhaled: Remove person to fresh air.

Seek medical attention if you feel unwell. Wash contaminated clothing before reuse.

Absorb spillage to prevent further locale exposure and personal contact.

Likely routes of exposure: Eyes, skin, inhalation and ingestion

Most important symptoms and effects, both acute and delayed:

May cause serious eye irritation, redness, pain. May irritate skin possibly with redness, pain.

Acute Health Hazard Symptoms:

Eyes: May cause serious eye irritation, redness, pain.

Skin: May cause irritation, redness, pain.

Inhalation and

Ingestion: Possible irritation, pain.

Acute health hazards: Eye damage, skin irritation, possible respiratory irritation.

Chronic Effects: No data available

#### **SECTION 5: FIRE-FIGHTING MEASURES**

Flammable Limits in Air, (% By Volume): UPPER: Not determined. LOWER: Not determined.

Flash Point: 104°F. or 40°C.

Method Used: Small scale closed cup ASTM D3278

Autoignition Temperature: No data available

NFPA 704 Standard: HEALTH: 1 FLAMMABILITY: 2 INSTABILITY: 0 Extinguishing Media: Dry chemical, CO2, water spray or regular foam. Special Fire Fighting Procedures: Regular procedures as needed for solvent type fires.

Unusual Fire And Explosion Hazards: None known.

Hazardous Decomposition Products: May produce smoke, carbon monoxide, carbon dioxide.

## **SECTION 6: ACCIDENTAL RELEASE MEASURES**

Eliminate all sources of ignition in the vicinity.

Small spills may be wiped, large spills use inert absorbent material.

## **SECTION 7: HANDLING AND STORAGE**

Store in well ventilated place. Keep cool. Store locked up. Close containers when not in use; do not contaminate; if stored outdoors, use protective covering. Do not store in standing water. Do not reuse container.

## SECTION 8: EXPOSURE CONTROLS / PERSONAL PROTECTION

COMPONENTS WITH EXPOSURE LIMITS:

CHEMICAL: Petroleum distillates

CAS# Proprietary
OSHA PEL-TWA: 500 ppm
ACGIH TLV-TWA: 200 ppm

Engineering Controls: As required to provide normal air flow. Ventilation: Local exhaust is recommended.

Respiratory Protection: Under normal use conditions a respirator should not be necessary, subject to local plant regulations; however, under

conditions of excessive airborne concentrations, a NIOSH-approved respirator for organic vapors is recommended.

Eye Protection: Safety glasses or splash-proof goggles and/or face shield recommended.

Skin Protection: Chemical resistant gloves; latex or neoprene recommended.

Other Protective Gear: Proper apparel to prevent unnecessary exposure to personnel.

Work Hygienic Practices: Normal plant procedures. Wash hands upon leaving work area. Launder clothes before reuse.

Page 2 of 4 Revised July 2018: Effective 7/02/2018

## **SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**

Appearance: Clear, near colorless liquid

Odor: Solvent

Odor threshold; No data available pH: Not applicable

Melting / freezing point: Less than 25°F. or -4°C. Initial boiling point and boiling range; Greater than 300°F. or 148°C.

Flash point: 104°F. or 40°C. Evaporation rate (n-butyl acetate = 1): Less than 0.12 Flammability: No data available Upper / lower flammability or explosive limits: No data available

Vapor pressure: Less than 1.6 mmHg @68°F./ 20°C.

Vapor density: Less than 6

Relative density: 0.80 (6.71 Lbs/Gallons or 804 grams/Liter)

Solubility in water;
Partition coefficient; n-octanol water:
No data available
Viscosity:
Robert than 2 cps

## **SECTION 10: STABILITY AND REACTIVITY**

Stability: Stable

Reactivity:

Conditions to Avoid:

Incompatibility (Material to Avoid):

No data available

Welding arcs, open flame

Strong oxidizing agents

Hazardous Decomposition or By-Products: May produce smoke, carbon monoxide, carbon dioxide

Hazardous Polymerization: Cannot occur. Conditions to Avoid (Polymerization): None known

## **SECTION 11: TOXICOLOGICAL INFORMATION**

Likely routes of exposure: Eyes, skin, ingestion and inhalation.

Acute Oral Toxicity Estimate: Greater than 2000 mg/kg
Acute Dermal Toxicity Estimate: Greater than 3000 mg/kg
Acute Inhalation Toxicity Estimate: No data available

Acute Health Hazard Symptoms:

Eyes: May cause serious eye irritation, redness, pain.

Skin: May cause irritation, redness, pain.

Inhalation and

Ingestion: Possible irritation, pain.

Acute health hazards: Eye damage, skin irritation, possible respiratory irritation.

Skin Corrosion / Irritation:
Serious Eye Damage / Eye Irritation:
Respiratory Or Skin Sensitization:
Germ Cell Mutagenicity:
Reproductive Toxicity:

No data available
No data available
No data available

Specific Target Organ Toxicity Single Exposure: No data available Specific Target Organ Toxicity Repeated or Prolonged Exposure: No data available

Aspiration Hazard: No data available

Chronic Effects: No data available Medical Conditions Generally Aggravated By Exposure:

Pre-existing problems caused by solvents

Carcinogenicity: OSHA: No NTP: No IARC: No

## **SECTION 12: ECOLOGICAL INFORMATION**

No data available.

# SPRAY / WIPE™

Continued

## **SECTION 13: DISPOSAL CONSIDERATIONS**

Dispose in accordance with local, state and federal regulations.

#### **SECTION 14: TRANSPORT INFORMATION**

U.S. DEPARTMENT OF TRANSPORTATION: (Land)

Proper Shipping Name / Hazard Class: ID Number: Packing Group: Label Statement:

NA1993, Combustible liquid, n.o.s. (petroleum distillates), PG III Ground transportation exception under CFR49 173.150

Emergency Response Guidebook: Guide 128

#### **SECTION 15: REGULATORY INFORMATION**

U.S. Federal Regulations

TSCA: All ingredients listed CERCLA: Not applicable.

SARA TITLE III:

313 Reportable Ingredients: Glycol ethers N230 at 10% (upper bound by weight)

HAP's (Hazardous Air Pollutants): Less than 0.71 Lbs/Gallon

California Regulations:

This product may contain trace amounts of chemicals known to the state of California to cause cancer Prop 65:

and birth defects or other reproductive harm.

SCAQMD Rule 443.1 851 g VOC/Liter or 7.1 Lbs/Gallon

SCAQMD Rule 443.1 Vapor pressure less than 1.6 mmHg @20°C.

International Regulations: No data available

## **SECTION 16: OTHER INFORMATION**

HMIS Rating: HEALTH: 1 FLAMMABILITY: 2 REACTIVITY: 0

Prepared by Intercontinental Chemical Corporation on 7/2/2018. Preparation Information:

Disclaimer: Intercontinental Chemical Corporation believes that the data contained herein are factual, however no warranty, express or implied, is made concerning the accuracy of the information.

> Page 4 of 4 Revised July 2018: Effective 7/02/2018